



HAMMERED METAL Brush & Spray Paints

DESCRIPTION	A metal finish that provides a long-lasting protective barrier that seals out moisture and protects the underlying surface from rust and corrosion. For use on metal, wood, concrete, stone and more. Do not apply to galvanized metal surfaces.		
APPEARANCE	A unique hammered texture that covers imperfect surfaces and offers a decorative finish.		
PACKAGING	Gallon (3.79 l) Black only, Quart (0.94 l) and 12 oz. (340 g) sprays cans		
SURFACE PREPARATION	Remove loose rust and loose paint with a wire brush or sandpaper. It is not necessary to remove tightly adhering rust or old paint. Clean surface with soap and water to remove all dirt, grease, oil or other contamination. Rinse thoroughly with fresh water and allow to fully dry. Lightly sand glossy surfaces and wipe away residual dust with a clean cloth. Do not use a primer.		
APPLICATION	Use in a properly ventilated area. Do not use near an open flame. Gallons/Quarts: Apply 2 coats for full coverage, best appearance, and maximum rust protection using a brush or roller. Sprays: Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin from overspray. Shake can vigorously for one minute after the mixing ball begins to rattle. Shake often during use. Hold can upright 12-16 inches (30-40 cm) from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance for the surface and in motion while spraying. Two or more coats may be necessary to eliminate pinholes and spots where moisture can penetrate. Make sure that corners, edges and heavily pitted areas are adequately covered.		
CLEAN-UP	Gallons/Quarts: Clean brush and roller and other tools with a xylene thinner immediately after use. Sprays: When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other object into the stem. Throw away empty in trash pickup. Do not burn or place in home trash compactor.		
PHYSICAL PROPERTIES	(Calculated values are shown and may vary slightly from the actual manufactured material)		
RESIN TYPE	Modified Alkyd		
VOLATILE ORGANIC COMPOUNDS	Gallon:<450 grams per liter (3.75 lbs/gal); Spray:< 80% by weight; Quart exempt		
PRACTICAL COVERAGE	Gallons: Approximately 320 sq.ft. (29.7 m ²) Quarts: Approximately 80 sq. ft. (7.4 m ²) Sprays: Approximately 20 sq. ft. (1.9 m ²)		
DRY TIMES @70° F (21°C) and 50% HUMIDITY	<u>Gallons/Quarts</u>	<u>Sprays</u>	
	Tack free	30 minutes	15 minutes
	Handle	4 hours	90 minutes
	Recoat	within 4 hours or after 7 days	within 1 hour or after 48 hours
FLASH POINT	52° F (11° C) Quarts and Gallons		-156° F (-144° C) Sprays
LEAD FREE			