

SPEED CHART AND GRAPH FOR SHOPSMITH MK V BELT AS MEASURED ON BELT INSIDE SURFACE, CENTROID, AND OUTSIDE SURFACE					
BELT LENGTH AS MEASURED (INCHES)		PD MOTOR	PD IDLER	DIAL	RPM
AS MEASURED ON BELT INSIDE SURFACE	24.41	1.12	4.88	SLOW	497
		1.59	4.53	C	758
		2.06	4.15	F	1070
		2.53	3.75	I	1456
		3.00	3.31	L	1955
		3.47	2.83	O	2643
		3.94	2.31	R	3673
		4.41	1.74	U	5452
		4.88	1.12	FAST	9356
AS MEASURED THROUGH BELT CENTROID	25.49	1.47	5.22	SLOW	607
		1.94	4.87	C	858
		2.41	4.49	F	1155
		2.88	4.09	I	1517
		3.34	3.66	L	1972
		3.81	3.18	O	2586
		4.28	2.66	R	3469
		4.75	2.09	U	4892
		5.22	1.47	FAST	7661
AS MEASURED ON BELT OUTSIDE SURFACE	26.38	1.75	5.50	SLOW	686
		2.22	5.15	C	929
		2.69	4.77	F	1213
		3.16	4.37	I	1558
		3.62	3.94	L	1985
		4.09	3.46	O	2550
		4.56	2.94	R	3343
		5.03	2.37	U	4569
		5.50	1.75	FAST	6781

